

SPECIFICATIONS

Headliner™ 115 Bass Cabinet



Frequency response, 1 meter on-axis, swept-sine in anechoic environment:

45 Hz to 4.1 kHz

Power handling:

250W RMS
500W program
1000W peak

Transducer complement:

15" Sheffield® woofer, Pro 1500+

Impedance (Z):

8 ohms

Input connections:

One 4-pin twist-lock connector, in parallel with two 1/4" phone jacks.

Enclosure:

Internally braced cabinet in black carpet, with a full coverage 16 ga. perforated metal grille.

Transport provisions:

Steel handles, one on each side

Dimensions (H x W x D):

24.00" x 23.38" x 18.38
610 mm x 594 mm x 467 mm

Net weight:

63 Lbs. (28.6 kg)

Features:

- 15" Sheffield® bass woofer
- 500 watts program power handling
- Vented cabinet for powerful bass
- Internal cabinet bracing
- Two 1/4" input jacks, and one 4-pin twist-lock connector
- 8 ohm impedance
- Durable black carpet covering
- 16 gauge perforated metal grille with black finish
- Steel corners for road durability

Description:

The new Headliner™ series has been re-designed from the ground up for the serious bass player on a budget. Voiced for strong bass with a smooth harmonic tone, the versatility and performance of the Headliner™ 115 encourages use with any fine bass amp head.

The Headliner™ 115 is constructed using internal bracing, and is covered with road-worthy black carpet. Steel corners protect the cabinet from the rigors of the road. The cabinet includes a black powdercoat finished 16 gauge perforated metal grille.

The 15" Sheffield® bass woofer provides a classic bass tone, with good power handling and punch. The vented cabinet provides powerful bass, with every note propelled forward into the mix. Inputs include two 1/4" input phone jacks, and one 4-pin twist-lock connector for maximum flexibility.

With a nominal impedance of 8 ohms, and a power handling of 500 watts program and 1000 watts peak, the Headliner™ 115 can be used in conjunction with any reasonably sized bass amp head. With the 8 ohm impedance, the Headliner™ 115 can be easily used with a Headliner™ 210 cabinet stacked on top, resulting in a 4 ohm total load. Be sure to check the amplifier specifications to verify the minimum impedance rating of the amp used to power the stacked pair of speakers.

3 + 2 YEAR LIMITED WARRANTY

NOTE: For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P.O. Box 2898, Meridian, Mississippi 39301-2898, or on our website at <http://www.peavey.com/support/warrantyregistration/warrantytext.cfm>.



Logo referenced in Directive 2002/96/EC Annex IV (OJ(L)37/38, 13.02.03 and defined in EN 50419: 2005
The bar is the symbol for marking of new waste and is applied only to equipment manufactured after 13 August 2005

Features and specifications subject to change without notice.

Peavey Electronics Corporation • 5022
Hartley Peavey Drive • Meridian, MS • 39305
(601) 483-5365 • FAX (601) 486-1278
www.peavey.com ©2010 EX000077

