

# 1505-8 BW™



INNOVATION. AMPLIFIED.™

## OVERVIEW

1505-8 BW™

## FEATURES

- Impedance: 8 Ohms
- Power capacity: 1400 W Peak 700 W Program 350 W Continuous
- Sensitivity: 97.9 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 17 lbs. / 7.7 kg
- Znom (ohms) 8
- Revc (ohms) 5.67
- Sd (Square Meters) 0.084
- BL (T/M) 16.90
- Fo (Hz) 46.5
- Vas (liters) 164.3
- Cms (uM/N) 164.0
- Mms (gm) 71.40
- Qms 6.50
- Qes 0.414
- Qts 0.389
- Xmax (mm) 5.1
- SPL (1W 1m) 97.9
- No (%) 3.90%
- Vd (cu. in. / ml) 26.1 / 428
- Pmax (Watts pgm.) 700
- Disp (cu. in. / ml) 197/ 3229
- Le (mH) 0.32
- 15"
- Weight Unpacked: 17.50 lb(7.938 kg)
- Weight Packed: 23.00 lb(10.433 kg)
- Width Packed: 21.25"(53.975 cm)
- Height Packed: 22.5"(57.15 cm)
- Depth Packed: 9.5"(24.13 cm)