

# Sheffield® TVX 1035-4



INNOVATION. AMPLIFIED.™

## OVERVIEW

Sheffield® TVX 1035-4

## FEATURES

- 10"
- Impedance: 4 Ohms
- Power capacity: 300 W Peak 150 W Program 75 W Continuous
- Sensitivity: 91.4 dB / 1W 1m
- Usable frequency range: 60 Hz ~ 4 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 1.75" / 44.4 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 7.4 lbs. / 3.4 kg
- Znom (ohms) 4
- Revc (ohms) 3.03
- Sd (Square Meters) 0.335
- BL (T/M) 7.97
- Fo (Hz) 44.7
- Vas (liters) 51.7
- Cms (uM/N) 325.2
- Mms (gm) 39.00
- Qms 4.18
- Qes 0.520
- Qts 0.460
- Xmax (mm) 2.5
- Le (mH) 0.11
- SPL (1W 1m) 91.4
- No (%) 0.9%
- Vd (cu. in. / ml) 5.1 / 84
- Pmax (Watts pgm.) 150
- Disp (cu. in. / ml) 83 / 1360
- Weight Unpacked: 4.00 lb(1.814 kg)
- Weight Packed: 7.00 lb(3.175 kg)
- Width Packed: 15.25"(38.735 cm)
- Height Packed: 16"(40.64 cm)
- Depth Packed: 6.25"(15.875 cm)