

# Blue Marvel® Pro 1056-8



INNOVATION. AMPLIFIED.™

## OVERVIEW

Blue Marvel® Pro 1056-8

## FEATURES

- 10"
- Impedance: 8 Ohms
- Power capacity: 600 W Peak 300 W Program 150 W Continuous
- Sensitivity: 93.0 dB /1W 1m
- Usable frequency range: 40 Hz ~ 4 kHz
- Cone: Impregnated cellulose
- Voice coil diameter: 2.0" / 51 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 12.5 lbs. / 5.7 kg
- Znom (ohms) 8
- Revc (ohms) 6.00
- Sd (Square Meters) 0.035
- BL (T/M) 12.79
- Fo (Hz) 40.3
- Vas (liters) 70.0
- Cms (uM/N) 404.4
- Mms (gm) 38.50
- Qms 9.80
- Qes 0.358
- Qts 0.345
- Xmax (mm) 4.0
- Le (mH) 0.64
- SPL (1W 1m) 93.0
- No (%) 1.24%
- Vd (cu. in. / ml) 8.5 / 140
- Pmax (Watts pgm.) 300
- Disp (cu. in. / ml) 87 / 1426
- Weight Unpacked: 4.00 lb(1.814 kg)
- Weight Packed: 7.00 lb(3.175 kg)
- Width Packed: 15.25"(38.735 cm)
- Height Packed: 16"(40.64 cm)
- Depth Packed: 6.25"(15.875 cm)