

Blue Marvel® BAM-1038



INNOVATION. AMPLIFIED.™

OVERVIEW

Blue Marvel® BAM-1038

FEATURES

- 10"
- Impedance: 8 Ohms
- Power capacity: 600 W Peak 300 W Program 150 W Continuous
- Sensitivity: 93.8 dB /1W 1m
- Usable frequency range: 50 Hz ~ 4 kHz
- Cone: Impregnated cellulose
- Voice coil diameter: 2.0" / 51 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 8.0 lbs. / 3.6 kg
- Znom (ohms) 8
- Revc (ohms) 6.10
- Sd (Square Meters) 0.035
- BL (T/M) 12.82
- Fo (Hz) 46.9
- Vas (liters) 49.2
- Cms (uM/N) 295.0
- Mms (gm) 39.10
- Qms 10.83
- Qes 0.480
- Qts 0.440
- Xmax (mm) 4.0
- Le (mH) 0.44
- SPL (1W 1m) 93.8
- No (%) 1.50%
- Vd (cu. in. / ml) 8.5 / 140
- Pmax (Watts pgm.) 300
- Disp (cu. in. / ml) 89 / 1459
- Weight Unpacked: 4.00 lb(1.814 kg)
- Weight Packed: 7.00 lb(3.175 kg)
- Width Packed: 15.25"(38.735 cm)
- Height Packed: 16"(40.64 cm)
- Depth Packed: 6.25"(15.875 cm)