

# Blue Marvel® Combo-1580



INNOVATION. AMPLIFIED.™

## OVERVIEW

Blue Marvel® Combo-1580

## FEATURES

- 15"
- Impedance: 4 Ohms
- Power capacity: 1200 W Peak 600 W Program 300 W Continuous
- Sensitivity: 97.1 dB / 1 W 1 m
- Usable frequency range: 45 Hz ~ 2.8 kHz
- Cone: Impregnated cellulose
- Voice coil diameter: 3.0" / 76 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 20.8 lbs. / 9.5 kg
- Znom (ohms) 4
- Revc (ohms) 3.59
- Sd (Square Meters) 0.051
- BL (T/M) 13.75
- Fo (Hz) 45.5
- Vas (liters) 156.9
- Cms (uM/N) 152.0
- Mms (gm) 80.40
- Qms 6.76
- Qes 0.440
- Qts 0.410
- Xmax (mm) 3.9
- Le (mH) 1.07
- SPL (1W 1m) 97.10
- No (%) 3.26%
- Vd (cu. in. / ml) 12.1 / 199
- Pmax (Watts pgm.) 600
- Disp (cu. in. / ml) 206 / 3376
- Weight Unpacked: 11.50 lb(5.216 kg)
- Weight Packed: 14.50 lb(6.577 kg)
- Width Packed: 18.25"(46.355 cm)
- Height Packed: 19"(48.26 cm)
- Depth Packed: 7"(17.78 cm)