

# Blue Marvel® TNT-1556



INNOVATION. AMPLIFIED.™

## OVERVIEW

Blue Marvel® TNT-1556

## FEATURES

- 15"
- Impedance: 4 Ohms
- Power capacity: 900 W Peak 450 W Program 225 W Continuous
- Sensitivity: 96.7 dB / 1W 1m
- Usable frequency range: 40 Hz ~ 3.5 kHz
- Cone: Impregnated cellulose
- Voice coil diameter: 2.5" / 63.5 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 13.4 lbs. / 6.1 kg
- Znom (ohms) 4
- Revc (ohms) 3.75
- Sd (Square Meters) 0.051
- BL (T/M) 12.65
- Fo (Hz) 40.6
- Vas (liters) 198.8
- Cms (uM/N) 193.0
- Mms (gm) 79.50
- Qms 6.99
- Qes 0.480
- Qts 0.450
- Xmax (mm) 3.2
- Le (mH) 0.89
- SPL (1W 1m) 96.7
- No (%) 2.93%
- Vd (cu. in. / ml) 10.0 / 163
- Pmax (Watts pgm.) 450
- Disp (cu. in. / ml) 192 / 3147
- Weight Unpacked: 11.50 lb(5.216 kg)
- Weight Packed: 14.50 lb(6.577 kg)
- Width Packed: 18.25"(46.355 cm)
- Height Packed: 19"(48.26 cm)
- Depth Packed: 7"(17.78 cm)