

# Sheffield® 1056-8



INNOVATION. AMPLIFIED.™

## OVERVIEW

Sheffield® 1056-8

## FEATURES

- 10"
- Impedance: 8 Ohms
- Power capacity: 700 W Peak 350 W Program 175 W Continuous
- Sensitivity: 94.6 dB / 1 W 1 m
- Usable freq. range: 50 Hz ~ 3.5 kHz
- Cone: Impregnated cellulose
- Voice coil diameter: 2.0" / 51 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 10 lbs. / 4.8 kg
- Znom (ohms) 8
- Revc (ohms) 6.32
- Sd (Square Meters) 0.036
- BL (T/M) 13.94
- Fo (Hz) 41.0
- Vas (liters) 73.8
- Cms (uM/N) 463.0
- Mms (gm) 32.50
- Qms 9.31
- Qes 0.723
- Qts 0.265
- Xmax (mm) 2.7
- Le (mH) 0.45
- SPL (1W 1m) 94.7
- No (%) 1.81%
- Vd (cu. in. / ml) 5.5 / 90
- Pmax (Watts pgm.) 350
- Disp (cu. in. / ml) 87 / 1426
- Weight Unpacked: 4.00 lb(1.814 kg)
- Weight Packed: 7.00 lb(3.175 kg)
- Width Packed: 15.25"(38.735 cm)
- Height Packed: 16"(40.64 cm)
- Depth Packed: 6.25"(15.875 cm)