

1008-8 HE BWX™



INNOVATION. AMPLIFIED.™

OVERVIEW

1008-8 HE BWX™

FEATURES

- Impedance: 8 Ohms
- Power capacity: 2000 W Peak 1000 W Program 500 W Continuous
- Sensitivity: 96.5 dB / 1 W 1 m
- Usable freq. range: 60 Hz ~ 4 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire fiberglass former Nomex® stiffener solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 14.7 lbs. / 6.7 kg
- Znom (ohms) 8
- Revc (ohms) 5.58
- Sd (Square Meters) 0.034
- BL (T/M) 16.18
- Fo (Hz) 62.0
- Vas (liters) 26.0
- Cms (uM/N) 163.9
- Mms (gm) 40.20
- Qms 7.41
- Qes 0.316
- Qts 0.303
- Xmax (mm) 2.2
- Le (mH) 0.37
- SPL (1W 1m) 95.9
- No (%) 1.90%
- Vd (cu. in. / ml) 7.7 / 127
- Pmax (Watts pgm.) 1000
- Disp (cu. in. / ml) 143 / 2345
- 10"
- Weight Unpacked: 15.43 lb(7 kg)
- Weight Packed: 19.00 lb(8.619 kg)
- Width Packed: 15.5"(39.37 cm)
- Height Packed: 16.75"(42.545 cm)
- Depth Packed: 7.25"(18.415 cm)