

# Sheffield® Pro 1200+™



INNOVATION. AMPLIFIED.™

## OVERVIEW

Sheffield® Pro 1200+™

## FEATURES

- 12"
- Revc (ohms) 5.21
- Sd (Square Meters) 0.052
- BL (T/M) 13.89
- Znom (ohms) 8
- Vas (liters) 70.0
- Cms (uM/N) 179.2
- Mms (gm) 49.96
- Qms 6.75
- Qes 0.451
- Net weight lb. / kg: 11 lbs. / 5.0 kg
- Qts 0.423
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Xmax (mm) 3.6
- Voice coil diameter: 2.5" / 63.5 mm
- Le (mH) 0.33
- Cone: Impregnated cellulose
- SPL (1W 1m) 96.3
- Usable freq. range: 50 Hz ~ 4 kHz
- No (%) 2.25%
- Sensitivity: 96.3 dB / 1 W 1 m
- Vd (cu. in. / ml) 22.3/365
- Power capacity: 1000 W Peak 500 W Program 250 W Continuous
- Pmax (Watts pgm.) 500
- Impedance: 8 Ohms
- Disp (cu. in. / ml) 121 / 1983
- Fo (Hz) 53.2
- Weight Unpacked: 11.00 lb(4.99 kg)
- Weight Packed: 13.01 lb(5.9 kg)
- Width Packed: 6.37"(16.1798 cm)
- Height Packed: 13.75"(34.925 cm)
- Depth Packed: 13.25"(33.655 cm)