

# 15" Low Rider® Subwoofer



INNOVATION. AMPLIFIED.™

## OVERVIEW

15" Low Rider® Subwoofer

## FEATURES

- Impedance: 8 Ohms
- Power capacity: 3200 W Peak 1600 W Program 800 W Continuous
- Sensitivity: 93.6 dB
- Usable freq. range: 30 Hz ~ 1 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Polyimide coated copper ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 21 lbs. / 9.5 kg
- Znom (ohms) 8
- Revc (ohms) 6.21
- Sd (Square Meters) 0.084
- BL (T/M) 22.73
- Fo (Hz) 33.9
- Vas (liters) 155.1
- Cms (uM/N) 154.8
- Mms (gm) 142.30
- Qms 10.67
- Qes 0.364
- Qts 0.352
- Xmax (mm) 9.6
- Le (mH) 0.82
- SPL (1W 1m) 93.6
- No (%) 1.33%
- Vd (cu. in. / ml) 98.3 / 1611
- Pmax (Watts pgm.) 1600
- Disp (cu. in. / ml) 204 / 3344
- 15" Subwoofer
- Weight Unpacked: 21.03 lb(9.54 kg)
- Weight Packed: 23.41 lb(10.62 kg)
- Width Packed: 21"(53.34 cm)
- Height Packed: 22"(55.88 cm)
- Depth Packed: 7"(17.78 cm)