

1801-4 LT BW™



INNOVATION. AMPLIFIED.™

OVERVIEW

1801-4 LT BW™

FEATURES

- Impedance: 4 Ohms
- Power capacity: 1400 W Peak 700 W Program 350 W Continuous
- Sensitivity: 97.5 dB / 1 W 1 m
- Usable freq. range: 35 Hz ~ 1 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 18 lbs. / 8.2 kg
- Znom (ohms) 4
- Revc (ohms) 3.72
- Sd (Square Meters) 0.124
- BL (T/M) 14.72
- Fo (Hz) 37.3
- Vas (liters) 335.6
- Cms (uM/N) 154.4
- Mms (gm) 117.80
- Qms 8.19
- Qes 0.474
- Qts 0.448
- Xmax (mm) 2.6
- Le (mH) 0.20
- SPL (1W 1m) 97.5
- No (%) 3.57%
- Vd (cu. in. / ml) 39.2 / 642
- Pmax (Watts pgm.) 700
- Disp (cu. in. / ml) 228 / 3737
- 18"
- Weight Unpacked: 17.50 lb(7.938 kg)
- Weight Packed: 21.37 lb(9.695 kg)
- Width Packed: 21"(53.34 cm)
- Height Packed: 22"(55.88 cm)
- Depth Packed: 7"(17.78 cm)