

1508-4 SPS BWX™



INNOVATION. AMPLIFIED.™

OVERVIEW

1508-4 SPS BWX™

FEATURES

- Impedance: 4 Ohms
- Power capacity: 2000 W Peak 1000 W Program 500 W Continuous
- Sensitivity: 97.5 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 17 lbs. / 7.7 kg
- Znom (ohms) 4
- Revc (ohms) 3.30
- Sd (Square Meters) 0.084
- BL (T/M) 12.72
- Fo (Hz) 45.9
- Vas (liters) 163.6
- Cms (uM/N) 163.3
- Mms (gm) 73.50
- Qms 11.20
- Qes 0.433
- Qts 0.417
- Xmax (mm) 2.3
- Le (mH) 2.11
- SPL (1W 1m) 97.5
- No (%) 3.60%
- Vd (cu. in. / ml) 23.6 / 386
- Pmax (Watts pgm.) 1000
- Disp (cu. in. / ml) 197 / 3229
- 15"
- Weight Unpacked: 17.50 lb(7.938 kg)
- Weight Packed: 20.00 lb(9.072 kg)
- Width Packed: 18.25"(46.355 cm)
- Height Packed: 18.5"(46.99 cm)
- Depth Packed: 7"(17.78 cm)