

1508-8 CU BWX™



INNOVATION. AMPLIFIED.™

OVERVIEW

1508-8 CU BWX™

FEATURES

- Impedance: 8 Ohms
- Power capacity: 2000 W Peak 1000 W Program 500 W Continuous
- Sensitivity: 97.2 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Copper ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener
- Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 17 lbs. / 7.7 kg
- Znom (ohms) 8
- Revc (ohms) 5.91
- Sd (Square Meters) 0.084
- BL (T/M) 20.84
- Fo (Hz) 36.7
- Vas (liters) 199.6
- Cms (uM/N) 199.2
- Mms (gm) 93.90
- Qms 9.31
- Qes 0.295
- Qts 0.286
- Xmax (mm) 4.7
- Le (mH) 0.58
- SPL (1W 1m) 97.2
- No (%) 3.30%
- Vd (cu. in. / ml) 48.1 / 789
- Pmax (Watts pgm.) 1000
- Disp (cu. in. / ml) 197/ 3229
- 15"
- Weight Unpacked: 17.50 lb(7.938 kg)
- Weight Packed: 20.37 lb(9.242 kg)
- Width Packed: 21"(53.34 cm)
- Height Packed: 22"(55.88 cm)
- Depth Packed: 7"(17.78 cm)