

1508-8 HE BWX™



INNOVATION. AMPLIFIED.™

OVERVIEW

1508-8 HE BWX™

FEATURES

- Impedance: 8 Ohms
- Power capacity: 2000 W Peak 1000 W Program 500 W Continuous
- Sensitivity: 100.3 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 17 lbs. / 7.7 kg
- Znom (ohms) 8
- Revc (ohms) 5.32
- Sd (Square Meters) 0.084
- BL (T/M) 16.04
- Fo (Hz) 51.2
- Vas (liters) 182.4
- Cms (uM/N) 182.0
- Mms (gm) 52.90
- Qms 10.60
- Qes 0.352
- Qts 0.341
- Le (mH) 0.34
- SPL (1W 1m) 100.3
- No (%) 6.70%
- Vd (cu. in. / ml) 19.5 / 319
- Pmax (Watts pgm.) 1000
- Disp (cu. in. / ml) 197/ 3229
- Xmax (mm) 1.9
- 15"
- Weight Unpacked: 16.75 lb(7.6 kg)
- Weight Packed: 23.00 lb(10.433 kg)
- Width Packed: 21.25"(53.975 cm)
- Height Packed: 22.5"(57.15 cm)
- Depth Packed: 9.5"(24.13 cm)