

# 1502-4 BW™



INNOVATION. AMPLIFIED.™

## OVERVIEW

1502-4 BW™

## FEATURES

- Impedance: 4 Ohms
- Power capacity: 1400 W Peak 700 W Program 350 W Continuous
- Sensitivity: 98.4 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 17 lbs. / 7.7 kg
- Znom (ohms) 4
- Revc (ohms) 3.66
- Sd (Square Meters) 0.084
- BL (T/M) 13.32
- Fo (Hz) 46.3
- Vas (liters) 179.6
- Cms (uM/N) 179.2
- Mms (gm) 65.90
- Qms 6.69
- Qes 0.396
- Qts 0.373
- Xmax (mm) 2.7
- Le (mH) 0.17
- SPL (1W 1m) 98.4
- No (%) 4.38%
- Vd (cu. in. / ml) 13.8 / 227
- Pmax (Watts pgm.) 700
- Disp (cu. in. / ml) 197/ 3229
- 15"
- Weight Unpacked: 17.50 lb(7.938 kg)
- Weight Packed: 23.00 lb(10.433 kg)
- Width Packed: 21.25"(53.975 cm)
- Height Packed: 22.5"(57.15 cm)
- Depth Packed: 9.5"(24.13 cm)