

1505-8 KA DT BW™



INNOVATION. AMPLIFIED.™

OVERVIEW

1505-8 KA DT BW™

FEATURES

- Impedance: 8 Ohms
- Power capacity: 1400 W Peak 700 W Program 350 W Continuous
- Sensitivity: 99.0 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 17 lbs. / 7.7 kg
- Znom (ohms) 8
- Revc (ohms) 5.23
- BL (T/M) 17.70
- Fo (Hz) 50.8
- Vas (liters) 143.5
- Cms (uM/N) 143.3
- Mms (gm) 68.50
- Qms 7.60
- Qes 0.367
- Qts 0.350
- Xmax (mm) 0.9
- Le (mH) 0.28
- SPL (1W 1m) 99.0
- No (%) 4.50%
- Vd (cu. in. / ml) 4.6 / 76
- Pmax (Watts pgm.) 700
- Disp (cu. in. / ml) 197/ 3229
- Sd (Square Meters) 0.084
- 15"
- Weight Unpacked: 17.50 lb(7.938 kg)
- Weight Packed: 20.37 lb(9.242 kg)
- Width Packed: 21"(53.34 cm)
- Height Packed: 22"(55.88 cm)
- Depth Packed: 7"(17.78 cm)