

1203-8 BW™



INNOVATION. AMPLIFIED.™

OVERVIEW

1203-8 BW™

FEATURES

- Impedance: 8 Ohms
- Power capacity: 1400 W Peak 700 W Program 350 W Continuous
- Sensitivity: 98.3 dB / 1 W 1 m
- Usable freq. range: 55 Hz ~ 4 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 16 lbs. / 7.3 kg
- Znom (ohms) 8
- Revc (ohms) 5.97
- Sd (Square Meters) 0.052
- BL (T/M) 18.44
- Fo (Hz) 58.4
- Vas (liters) 63.3
- Cms (uM/N) 165.0
- Mms (gm) 38.20
- Qms 7.63
- Qes 0.290
- Qts 0.280
- Xmax (mm) 0.30
- Le (mH) 0.33
- SPL (1W 1m) 98.3
- No (%) 4.20%
- Vd (cu. in. / ml) 0.95 / 15.6
- Pmax (Watts pgm.) 700
- Disp (cu. in. / ml) 109/ 1797
- 12"
- Weight Unpacked: 16.00 lb(7.257 kg)
- Weight Packed: 18.87 lb(8.561 kg)
- Width Packed: 15"(38.1 cm)
- Height Packed: 16"(40.64 cm)
- Depth Packed: 7"(17.78 cm)