

44XT™ w/o adapter Driver



OVERVIEW

44XT™ w/o adapter Driver

FEATURES

- 4"
- Throat Parameter: Standard: 1.6" / 40.6 mm Supplied without throat extension
- Nominal Impedance: 8 Ohms
- Minimum Impedance: 7.1 Ohms
- DC Resistance: 6.8 Ohms
- Power Capacity 500 Hz to 20,000 Hz: 320 W peak 160 W program 80 W continuous
- Sensitivity: 111 dB / 1 Watt 1 meter On-axis on a 80° H x 40° V horn
- Nominal Efficiency: 30%
- Frequency Response: 500 Hz to 20,000 Hz
- Recommended Crossover: 1,000 Hz
- Lowest Recommended Crossover: 500 Hz at 12 dB / Octave
- Diaphragm: Commercially pure titanium
- Voice Coil Diameter: 4" / 101 mm
- Voice Coil Material: Edge-wound aluminum ribbon with a composite bobbin
- Flux Density: 19,000 gauss (1.9T)
- Dimensions: 8.388" (213 mm)D x 3.63" (92 mm) H
- Net Weight: Standard: 18 lbs. / 9.5 kg
- Shipping Weight: Standard: 22 lbs. / 10 kg
- Weight Unpacked: 17.64 lb(8 kg)
- Weight Packed: 22.05 lb(10 kg)
- Width Packed: 11.75"(29.845 cm)
- Height Packed: 12.5"(31.75 cm)
- Depth Packed: 8.5"(21.59 cm)