

# 1208-8 SPS BWX™

## OVERVIEW

1208-8 SPS BWX™

## FEATURES

- Impedance: 8 Ohms
- Power capacity: 2000 W Peak 1000 W Program 500 W Continuous
- Sensitivity: 96.9 dB / 1 W 1 m
- Usable freq. range: 50 Hz ~ 3.5 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 16 lbs. / 7.3 kg
- Znom (ohms) 8
- Revc (ohms) 5.43
- Sd (Square Meters) 0.052
- BL (T/M) 15.13
- Fo (Hz) 56.1
- Vas (liters) 54.6
- Cms (uM/N) 142.2
- Mms (gm) 50.70
- Qms 9.51
- Qes 0.448
- Qts 0.428
- Xmax (mm) 4.70
- Le (mH) 0.36
- SPL (1W 1m) 96.9
- No (%) 3.10%
- Vd (cu. in. / ml) 29.8 / 488
- Pmax (Watts pgm.) 1000
- Disp (cu. in. / ml) 109 / 1797
- 12"
- Weight Unpacked: 16.09 lb(7.3 kg)
- Weight Packed: 17.20 lb(7.8 kg)
- Width Packed: 13.976"(35.49904 cm)
- Height Packed: 14.764"(37.50056 cm)
- Depth Packed: 5.315"(13.5001 cm)