

RX™22 CT Driver



FEATURES

- Throat Parameter: .960" / 24.38 mm
- Nominal Impedance: 8 Ohms
- Minimum Impedance: 7.7 Ohms
- DC Resistance: 7.0 Ohms
- Power Capacity 1200 Hz to 20,000 Hz: 160 W peak, 80 W program, 40 W continuous using pink noise band limited from 1000 Hz to 20 kHz (AES 2-1984)
- Sensitivity: 107 dB / 1W 1m On-axis on 90° H x 40° V horn
- Nominal Efficiency: 30%
- Frequency Response: 650 Hz to 20,000 Hz
- Recommended Crossover: 1200 Hz at 12 dB / Octave
- Lowest Recommended Crossover: 1000 Hz at 12 dB / Octave
- Diaphragm: Commercially pure titanium
- Voice Coil Diameter: 2.0" / 50.8 mm
- Voice Coil Material: Copper Clad Aluminum Wire with a High temp Kapton bobbin
- Voice Coil Cooling: Ferrofluid
- Flux Density: 18,000 gauss (1.8T)
- Dimensions: 5.02" (128 mm) diameter x 3.13" (80 mm) depth
- Horn Coupling Diameter: .960 (24.4 mm)
- Horn Coupling Threads: Standard 1 3/8" - 18"
- Weight Unpacked: 6.13 lb(2.78 kg)
- Weight Packed: 6.39 lb(2.9 kg)
- Width Packed: 5.75"(14.605 cm)
- Height Packed: 6.125"(15.5575 cm)
- Depth Packed: 3.625"(9.2075 cm)