

RX™ 22N Neo HF Driver



FEATURES

- 2"
- Throat Parameter: 0.875" / 22 mm
- Nominal Impedance: 8 Ohms
- Minimum Impedance: 5.2 Ohms
- DC Resistance: 5.1 Ohms
- Power Capacity 1000 Hz to 20,000 Hz: 280 W peak, 140 W program, 70 W continuous, using pink noise band limited from 1000 Hz to 20 kHz (AES 2-1984)
- Sensitivity: 111 dB / 1W 1m On-axis on 90° H x 45° V horn
- Nominal Efficiency: 30%
- Frequency Response: 500 Hz to 20,000 Hz
- Recommended Crossover: 1,200 Hz at 12 dB / Octave
- Lowest Recommended Crossover: 500 Hz at 12 dB / Octave
- Diaphragm: Commercially pure titanium
- Voice Coil Diameter: 2.0" / 50.8 mm
- Voice Coil Material: Edge-wound copper-clad aluminum ribbon with a high temp composite bobbin
- Voice Coil Cooling: Ferrofluid
- Flux Density: 20,500 gauss (2T)
- Dimensions: 3.858" (98 mm) diameter x 3.01" (76.4 mm) depth
- Horn Coupling Diameter: 7/8" (22.2 mm)
- Horn Coupling Threads: Standard 1 3/8" - 18"
- Net Weight: 2 lbs. 12 oz.
- Shipping Weight: 3 lbs. 11.5 oz.
- Diaphragm Kit: 03617300
- Weight Packed: 2.98 lb(1.35 kg)
- Width Packed: 4.5"(11.43 cm)
- Height Packed: 4.725"(12.0015 cm)
- Depth Packed: 3.55"(9.017 cm)