

Versarray™ 212 Line Array Speaker System



OVERVIEW

The Versarray™ 212 array is loaded with dual 12" Black Widow® Neo speakers with 4" voice coils, ten 2.5" neo midrange speakers arranged in two banks of five each, and four 4.75" planar dynamic ribbon tweeter line sources on a waveguide. Designed to provide modular coverage of medium to large venues and intended for use with the companion Versarray Sub models, the Versarray 212 offers extreme versatility in highly demanding performance situations. The low-frequency section handles 2,000 watts program, while the mid and high sections handle 400 watts program each.

FEATURES

- Low Frequency power handling: 2000 watts program, 4000 watts peak
- High Frequency power handling: 400 watts program, 800 watts peak
- Frequency Response: 70Hz - 20 kHz
- 90 x 15 coverage pattern (per line array module)
- Dual 12" vented Black Widow® Neo woofers with dual 4" voice coils
- Durable GatorHyde® finish
- Ten 2.5" NEO Midranges in dual line array source
- Two Neutrik® Speakon® 8-pin inputs in parallel
- Four Planer Ribbon Tweeters with NEO magnets on a manifold line source
- Weight Unpacked: 93.00 lb(42.184 kg)
- Weight Packed: 106.30 lb(48.216 kg)
- Width Packed: 16.75"(42.545 cm)
- Height Packed: 45"(114.3 cm)
- Depth Packed: 15.25"(38.735 cm)