

SP® 2 1000-Watt 2-Way PA Speaker



OVERVIEW

The SP® 2 two-way, full-range/bi-ampable Sound Reinforcement system features a premium 15" BWX Black Widow® 4" diameter VC woofer with field-replaceable basket, RX™ 22CT compression driver, and Sound Guard™ III tweeter protection. Engineered for optimal sound reproduction with proven reliability continuing a 30-year legacy, Peavey SP enclosures feature exclusive asymmetrical Quadratic Throat Waveguide™ technology that helps deliver pristine, precise sound. Asymmetrical horn aims the coverage pattern 15° upward and 35° downward - directing sound to your audience, not over their heads.

FEATURES

- Two-way, full-range/bi-ampable Sound Reinforcement system
- 64Hz to 17kHz
- Exclusive Quadratic Throat Waveguide™ technology
- 1,000 watts program, 2,000 watts peak
- Asymmetrical horn aims the sound down 10° (at the audience, not over their heads)
- RX™22CT compression driver
- Plywood finished in black textured paint
- Full length black powder coated metal grille
- 15" BWX Black Widow® 4" diameter VC woofer
- M8 threaded mounting suspension points (3 top, 3 bottom and 2 each side & 1 each top rear and bottom rear)
- Sound Guard™ III tweeter protection
- Built-in stand-mount adapter and four large rubber feet on bottom for floor use
- Full-range inputs include two 1/4" phone jacks, one four-pin, twist lock connector & one Neutrik NL4 Speakon switching jack (bi-amp only)
- Weight Packed: 61.00 lb(27.669 kg)
- Width Packed: 20"(50.8 cm)
- Height Packed: 30"(76.2 cm)
- Depth Packed: 20"(50.8 cm)