

# PRO 10

## OVERVIEW

PRO 10

## FEATURES

- Impedance: 8 Ohms
- Power capacity: 800 W Peak 400 W Program 200 W Continuous
- Sensitivity: 94.3 dB / 1 W 1 m
- Usable freq. range: 50 Hz ~ 4 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 2.5" / 63.5 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 9.5 lbs. / 4.3 kg
- Znom (ohms) 8
- Revc (ohms) 6.00
- Sd (Square Meters) 0.035
- BL (T/M) 14.33
- Fo (Hz) 67.7
- Vas (liters) 25.1
- Cms (uM/N) 150.0
- Mms (gm) 36.90
- Qms 2.85
- Qes 0.456
- Qts 0.395
- Xmax (mm) 2.5
- Le (mH) 0.72
- SPL (1W 1m) 94.3
- No (%) 1.70%
- Vd (cu. in. / ml) 10.6 / 173
- Pmax (Watts pgm.) 400
- Disp (cu. in. / ml) 95 / 1564
- 10"
- Weight Unpacked: 9.26 lb(4.2 kg)
- Weight Packed: 11.02 lb(5 kg)
- Width Packed: 11.125"(28.2575 cm)
- Height Packed: 12.125"(30.7975 cm)
- Depth Packed: 6.325"(16.0655 cm)